

Clean Copy

B1 2. (Twice Amended) The juvenile vehicle seat assembly of claim ~~12~~, wherein the cup holder includes a connecting member, the connecting member being movable relative to the base, and a cup receiver coupled to the connecting member to move therewith.

4. (Amended) The juvenile vehicle seat assembly of claim 2, wherein the base provides a receptor for the connecting member.

~~3~~ 5. (Amended) The juvenile vehicle seat assembly of claim 2 further comprising a detent carried on one of the base or the connecting member and a notch provided in the other of the base or the connecting member to inhibit movement of the cup holder from at least one of the first or second positions.

B2 ~~5~~ 6. (Amended) The juvenile vehicle seat assembly of claim 2, wherein the connecting member includes a detent, the base includes a notch, and the detent engages the notch to inhibit movement of the cup holder from the second position toward the first position.

~~6~~ 7. (Amended) The juvenile vehicle seat assembly of claim ~~5~~, wherein the base further includes an opening and the detent engages an edge of the opening to inhibit movement of the cup holder from the first position toward the second position.

~~7~~ 8. (Amended) The juvenile vehicle seat assembly of claim ~~6~~, wherein the connecting member further includes a catch that engages the edge of the opening to inhibit removal of the cup holder from the base.

B3 ~~13~~ 9. (Twice Amended) The juvenile vehicle seat assembly of claim ~~12~~, wherein a base connector includes a retainer and the base includes a first retainer engaging portion and a second retainer engaging portion, wherein the retainer engages the first retainer engaging portion to inhibit movement of the cup holder from the second position and the retainer engages the second retainer engaging portion to inhibit movement of the cup holder from the first position.

B33  
cont

14  
20

(Twice Amended) The juvenile vehicle seat assembly of claim ~~12~~, wherein a base connector includes a first retainer and a second retainer and the base includes a retainer engaging portion, wherein the first retainer engages the retainer engaging portion to inhibit movement of the cup holder from the first position and the second retainer engages the retainer engaging portion to inhibit movement of the cup holder from the base.

47  
58

46  
52

(Amended) The seat assembly of claim ~~52~~, wherein the retainer means further includes a second retainer coupled to the base connector and arranged to extend into the second opening formed in the deck to inhibit movement of the cupholder from the extended position to a withdrawn position outside of the cupholder receptor formed in the base upon movement of the cupholder to the extended position.

B4